

Calderas de Pie Sime - RMG / RS / AR / 1R / 2R / RONDO



RMG

Caldera a gas de hierro fundido con quemador atmosférico y encendido electrónico.
Potencia eléctrica: 16 w (excepto RMG 110 69w)

Modelo	Código	Potencia Térmica		Cap. lt	Peso kg
		Nominal kcal/H	Imput kcal/H		
RMG 70	00.160.73	60.300	67.000	27	238
RMG 80	00.160.74	67.700	75.200	30	266
RMG 90	00.160.75	77.400	86.000	33	294
RMG 100	00.160.76	84.800	94.200	36	322
RMG 110	00.160.77	92.800	103.600	37	350



RS

Caldera a gas de hierro fundido con quemador atmosférico y encendido electrónico.
Potencia eléctrica: 80 w

Modelo	Código	Potencia Térmica		Cap. lt	Peso kg
		Nominal kcal/H	Imput kcal/H		
RS 129	00.169.50	110.900	125.450	67,5	266
RS 151	00.169.51	129.500	146.200	77	294
RS 172	00.169.52	148.100	167.000	86,5	322
RS 194	00.169.53	166.600	187.650	96	757
RS 215	00.169.54	185.000	208.200	105,5	829
RS 237	00.169.55	203.400	228.750	115	904
RS 258	00.169.56	221.700	249.400	124,5	974
RS 279	00.169.57	240.000	269.000	134	1.044



AR - RONDO - 1R - 2R

Caldera a gas de hierro fundido para quemadores de petróleo/parafina o gas soplado.
Quemador no incluido.

Modelo	Código	Potencia Térmica		Cap. lt	Peso kg	Quem. Riello Sugerido	
		Nominal kcal/H	Imput kcal/H			Petróleo	Gas
AR - 4	00.169.61	25.300	29.400	23	122	40G5	40GS5
AR - 5	00.169.62	34.400	39.000	27	147	40G5	40GS5
RONDO - 6	00.169.63	41.400	45.600	24,8	186	40G5	40GS5
RONDO - 7	00.169.64	49.500	54.400	28,8	212	40G10	40GS10
1R - 7	00.169.67	63.600	71.500	42	293	40G10	40GS10
1R - 8	00.169.68	72.200	80.700	46,5	325	40G10	40GS10
1R - 9	00.169.69	80.200	88.900	51	357	40G10	40GS10
2R - 6	00.169.71	86.500	97.600	92	462	40G20	40GS20
2R - 7	00.169.72	106.500	119.600	107	520	40G20	40GS20
2R - 8	00.169.73	126.500	141.600	122	578	40G20	40GS20
2R - 9	00.169.74	142.000	158.300	136	636	40G20	40GS20
2R - 10	00.169.75	154.500	171.700	151	676	40G20	40GS20
2R - 11	00.169.76	170.000	188.900	165	734	40G20S	40GS20
2R - 12	00.169.77	183.500	203.900	180	792	RL28/1	RS28
2R - 13	00.169.78	198.000	220.000	194	850	RL28/1	RS28/1
2R - 14	00.169.82	214.000	237.000	209	908	RL28/1	RS28/1
2R - 15	00.169.79	229.500	255.200	223	966	RL28/1	RS28/1

